

# SEAL OF APPROVAL

## Polymer Concepts, Inc.

7425 Colony Ct, Cumming, Georgia 30041, United States

### EncapSoil-Guard

Dilution Rate (oz./gal.): 18oz./1gal.  
Application Rate (oz./ft<sup>2</sup>): 0.017oz./1 sq ft

Cleaning Instructions: For normal soil using CRB, mix 12 oz. of EncapSoil-Guard per gallon of hot water. For heavy soiled areas, mix 18 oz. of EncapSoil-Guard per gallon of hot water. Additional cleaning passes may be required. Scrub the carpet evenly to generate a light foam build-up simply whiten the surface of the carpet. A heavy foam build-up is NOT desirable. EncapSoil-Guard dries into soil-encapsulating crystals. Vacuum at the next scheduled vacuuming interval. No rinsing is required. Rinsing reduces the encapsulating and stain-resist properties of EncapSoil-Guard. The recommended spread rate is from 2,000 sq. ft. to 3,000 sq. ft. per concentrated gallon based on soil conditions and type of area being cleaned.

Cleaning Solution Program

Type: Encapsulate

Certification From: 07/23/2024

Certification Expiration: 09/30/2025



100 S HAMILTON STREET  
DALTON, GA 30720-4612  
UNITED STATES

SOA-certified products are required by the US Green Building Council's LEED v4.1 under the program's Green Cleaning Equipment provision.

Certification Number:  
**SOA100807**



WWW.CARPET-RUG.ORG