

SEAL OF APPROVAL

Hillyard, Inc.

302 N. 4th. St., St. Joseph, MO 64501, United States

Double Down

Dilution Rate (oz./gal.): RTU

Cleaning Instructions:

1. Pretest Double Down in an inconspicuous area to make certain the solution will not damage the carpet fiber or dye. Apply Double Down to the test area and hold a white cloth on the wet area for 10 seconds. Examine the white cloth and carpet for any color transfer, color change, or damage to the carpet. 2. Blot wet stains with a clean white cloth or paper towel. After removing any gross soils or debris, liberally spray Double Down on the spot and allow it to dwell for 60 seconds. 3. Agitate by working from the outside to the center of the spot with a carpet brush, bone knife or clean cloth. Repeat if necessary to completely remove the spot. 4. Flush with clean water and blot with a clean cloth.

Cleaning Solution Program

Certification From: 09/24/2024

Type: Spot Remover

Certification Expiration: 09/30/2025



THE CARPET AND RUG INSTITUTE

100 S HAMILTON STREET
DALTON, GA 30720-4612
UNITED STATES

SOA-certified products are required by the US Green Building Council's LEED v4.1 under the program's Green Cleaning Equipment provision.

Certification Number:

SOA100811



WWW.CARPET-RUG.ORG