

SEAL OF APPROVAL



Foaming Floors

4555 Goves Road, Columbus, OH 43232, United States

Foam Armor

Dilution Rate (oz./gal.): 12 oz /gallon of water
Application Rate (oz./ft²): 1 gal / 1000 sf

Cleaning Instructions: DIRECTIONS PLEASE NOTE: Before use always test a hidden section of the carpet for color fastness. Vacuum area to be treated first to remove any loose soil. For Spots and Stains on Carpets and Rugs: 1. Mix 12ounces of XL Fortify LMC concentrate with 1 gallon of water in a clean, standard pump sprayer. 2. Hold spray nozzle 12 to 18 inches from the carpet and apply the XL Fortify LMC solution to the entire area to be cleaned. Wet but do not saturate. 3. Work XL Fortify LMC into the carpet or rug using a counter rotating brush and allow time for drying.

Cleaning Solution Program

Type: Encapsulate

Certification From: 06/26/2026

Certification Expiration: 09/30/2027

100 S HAMILTON STREET
DALTON, GA 30720-4612
UNITED STATES

SOA-certified products are
required by the US Green
Building Council's LEED v4.1
under the program's Green
Cleaning Equipment provision.

Certification Number:

SOA100845



WWW.CARPET-RUG.ORG